

Revision date 1/10/2024

Copyright, 2023, American Standard Adhesives, Inc.

All rights reserved. Copying and/or downloading the information in this document is allowed for the purpose of properly utilizing American Standard Adhesives (ASA) products provided that: (1) the information is copied in full with no changes unless prior consent is obtained from ASA, and (2) neither the copy nor the original is resold or distributed to make a profit.

SECTION 1: IDENTIFICATION

Product code ASA-8802

Product class Glue granules based on EVA-copolymer

Intended use of the product Intended for industrial use with a hot melt equipment

Supplier information American Standard Adhesives, Inc.

5061 Brooks St. Ste B Montclair, CA 91763 USA

Toll Free: +1 877 272-4582 Fax: +1 866-232-1888

Email: Service@asaglue.com

SECTION 2: HAZARD(S) IDENTIFICATION

Chemical hazard class Not classified as hazardous according to OSHA Hazard

Communication Standard 29 CFR 1910.1200.

Label elements

Signal wordsNot applicableSymbolsNot applicablePictogramsNot applicable

Supplemental Information Wear protective gear for hands, face, eyes, and clothing while

handling materials in a molten state. Avoid contact with molten

hot melt, pre-melter, or applicator tip. Avoid direct eye exposure to vapors. In case of eye/skin contact with molten material, immediately flush with cold water and cover with a clean dressing. Do not attempt to remove molten material. Have a burn treated by a physician. May cause thermal burns.



Revision date 1/10/2024

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NO.	CONCENTRATION PERCENTAGE (%)
EVA (Ethylene Vinyl Acetate) copolymer	24937-78-8	45-70
Hydrogenated Hydrocarbon Resin	69430-35-9	30-45
Paraffin Wax	64742-43-4	0-10

SECTION 4: FIRST AID MEASURES

medical advice (show the label is possible).

Inhalation No need for first aid is anticipated. Non-molten glue is not

expected to have any adverse effects. If molten glue is inhaled, move to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical

advice.

Skin Contact Immediately flush skin with large amounts of cold water for at

least 15 minutes. DO NOT ATTEMPT TO REMOVE

SOLIDIFIED MATERIAL. Cover affected area with a clean

dressing. Get immediate medical attention.

Eye Contact Non-molten glue is not expected to have any adverse effect. If

molten glue contacts the eye, rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention immediately.

Ingestion No special measures are necessary. If you feel unwell, seek

medical attention.

Most important symptoms and effects, both acute and delayed

Ingredients are of low toxicity in nature. If it does have effects,

it will be on the central nervous system.



Revision date 1/10/2024

Indication of any immediate medical attention and special

If medical advice is needed, have product container label at

hand.

treatment needed

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media Fire-fighting procedures

Use CO2, extinguishing powder or water spray. Fight larger

fires with water spray or alcohol-resistant foam.

Advice for Firefighters
Precautionary measures
Protection during
firefighting

Exercise caution when fighting any chemical fire

Do not enter fire area without proper protective equipment,

including respiratory protection.

Hazardous decomposition or by-

products

<u>Substance</u> <u>Condition</u>

Carbon monoxide During combustion
Carbon dioxide During combustion

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Environmental precautions

Avoid release to the environment. Do not allow product to reach sewer system or open water. Prevent from spreading (e.g., by damming-in or oil barriers).

Methods and materials for containment and cleaning up

Absorb with liquid binding materials (sand, diatomite, acid binders, general-purpose binders, sawdust). Allow to solidify. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Ensure that suitable extractors/ventilation systems are available on processing machines and in the workplace. Avoid contact with oxidizing agents (e.g. chlorine, chromic acid, etc.)



Revision date 1/10/2024

Conditions for safe storage Store in cool, dry place in tightly closed containers. No more

than 140 °F (60°C) ambient temperature. Avoid direct contact

with sunlight or heat source. Store away from heat and

oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits No occupational exposure limit values exist for any of the

components listed in Section 3 of this SDS.

Personal protective equipment

(PPE)

Personal protective The standard precautionary measures for handling chemicals

equipment should be observed. Wash hands before breaks and at the

end of work. Avoid skin contact with the liquefied material.

Respiratory protection Not necessary if room is well-ventilated.

Skin/hand protection Not required.

Eye/face protection Select and use eye/face protection to prevent contact based

on the results of an exposure assessment. Full face shield and indirect vented goggles are recommended during refilling

and spraying.

Thermal hazardsWear heat insulating gloves when handling hot material to

prevent thermal burns.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and

chemical properties

Appearance Granule Color Clear white

PH value -

Odor None

Specific Gravity - [Ref std: Water = 1]

Solubility in water Insoluble

Vapor pressure (mmm Hg) Vapor density Evaporation rate -

Flash Point 536°F (280°C) Softening point 176°F (80°C)

Auto-ignition -



Revision date 1/10/2024

Lower/upper flammable limits
Flammability (solid, gas)
Decomposition temperature
Partition coefficient
(n-octanol/water)

SECTION 10: STABILITY AND REACTIVITY

Reactivity None known

Chemical stability Stable under recommended handling and storage conditions.

See <u>Section 7</u>.

Possible hazardous reactions The following conditions may increase the chance of fire and

explosion: static electricity, spark, fire, flammable material,

strong oxidant (e.g., peroxide, nitrate, perchlorate)

Conditions to avoid Prolong overheating

Possible hazard reactionToxic fumes may be released if heated above the

decomposition point. No dangerous reactions known.

Hazardous decomposition

products

Carbon dioxide, carbon monoxide, and organic vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological

effects

Based on test data and/or information on the components, this

material may produce the following health effects:

Signs and symptoms of exposure

Inhalation

No health effects are expected.

Skin contact During heating, contact with skin may lead to thermal burns that

include signs/symptoms of intense pain, redness, swelling, and

tissue destruction.

Eye contact During heating, contact with skin may lead to thermal burns that

include signs/symptoms of intense pain, redness, swelling, and

tissue destruction.

Ingestion No known health effects.



Revision date 1/10/2024

Additional toxicology information When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: ECOLOGICAL INFORMATION

No relevant information available **Aquatic toxicity**

Persistence and degradability No relevant information available

Behavior in environmental

systems

No relevant information available

Results of PBT and vPvB

assessment

No relevant information available

Other adverse effects Avoid release to the environment

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage disposal recommendations Do not dispose waste into sewer

Waste disposal recommendation

Must not be disposed together with household garbage. Dispose contents in accordance with the

local/regional/national/international regulations. Empty contaminated packaging thoroughly. They can be recycled after thorough and property cleaning. Packaging that cannot be cleaned are to be disposed off in the same manner as the

product.

Consult all relevant authorities and regulation prior to disposal to ensure proper classification. Use an approved industrial waste facility to dispose off waste products. As an alternative, an authorized waste incineration plan could be used as a method of disposal.

SECTION 14: TRANSPORT INFORMATION



Revision date 1/10/2024

In accordance with DOT In accordance with IMDG In accordance with IATA In accordance with TDG

Not regulated for transport Not regulated for transport Not regulated for transport Not regulated for transport

These transportation categories are offered as a convenience to the customer.

YOU, the shipper, are still in charge of adhering to all rules and legislation that may be in force, including the right packaging and transportation classification.

The transportation classes used by American Standard Adhesives (ASA) are determined by the product compositions, packaging, corporate policies, and ASA's understanding of the relevant current regulations. The accuracy of this classification information is not guaranteed by ASA. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original ASA package is certified for U.S. ground and ocean shipment only. If you are shipping by air, please verify the applicable regulatory requirements.

SECTION 15: REGULATORY INFORMATION

US federal regulationsThe components of this product are listed in the TSCA

Inventory.

US state regulationsNeither this product or its chemical components appear on

any US state lists.

Canadian regulations The components of this product are on the DSL inventory or

are exempt from listing.

International regulationsContact American Standard Adhesives for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200



Revision date 1/10/2024

SECTION 16: OTHER INFORMATION

Party responsible for the preparation of this document

American Standard Adhesives, Inc.

+ 1 909 673-9898

As of the date of issuance, it the information provided in this Safety Data Sheet is accurate. To the best of our knowledge and after careful preparation, it is truthful and correct. The recommendations and information provided for this product are given with the assumption that the purchaser will independently evaluate them.

DISCLAIMER: This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which American Standard Adhesives (ASA) assumes legal responsibility. The data is submitted for the user's information and considerations only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws, and regulations.

As a service, ASA offers its information in electronic format. In the rare instance that electronic transfer may result in errors, omissions, or alterations in this information, ASA makes no guarantees as to its accuracy or completeness this document. Data retrieved directly from ASA will always be the most complete and up-to-date information.